

north states®

*Quality Products
for the way you live*

INSTRUCTIONS FOR MODEL 4665



IMPORTANT: PLEASE KEEP FOR FUTURE REFERENCE!

For helpful tips and instructions, please visit our website: www.northstatesind.com or contact our Customer Care department via email: CustomerService@northstatesind.com
Phone: (763) 486-1754 or Toll Free: (800) 848-8421

WARNING

- Children have died or been seriously injured when gates are not properly secured.
- **ALWAYS** install and use gates as directed using all required parts.
- You **MUST** install wall cups to keep gate in place. Without wall cups, child can push out and escape.
- **STOP** using when a child can climb over or dislodge the gate.
- Install only with locking/latching mechanism securely engaged on side away from child.
- To prevent falls, **NEVER** use at top of stairs.
- **NEVER** use to keep child away from pool.
- This product will not necessarily prevent all accidents.
- **NEVER** leave child unattended.
- Periodically check all fasteners to be sure they are tight and secure, stop using gate if any parts are missing or become damaged.
- This gate is to be used in openings 29.5" to 50" (75 cm to 127 cm) only.

Installation and Operating Instructions:

No Tools Required

1. Place gate on floor and expand in the opening. Be sure to adhere the wall cups (door sockets) to the opening wall or surface where the four bumpers touch.
NOTE: Be sure to place the gate so the locking bar is on the side of the gate that will be away from the child.
2. Hold the panels firmly together at the top of the gate so that the panels are unable to move.
3. Pull the locking bar up 2 to 3 clicks and then lock down into place. This should put pressure on the 4 rubber bumpers holding the gate in place.
4. If the gate is loose in the opening, pull up 1 more click until you get a good solid fit in the opening. If the gate is too tight in the opening, do not force the locking bar down. This could put too much pressure on the gate, causing damage to your opening, the gate or both. (The locking bar should have a slight bow.) However if the bow is too large, simply lift up on the locking bar and press the white button on the latch to reduce the width of the gate.
5. To open the gate, simply lift up on the locking bar and remove the gate from the opening.

Care and Maintenance

To clean: Wipe with a clean, soft, damp cloth and dry thoroughly. Do not use harsh or abrasive cleaners. Always keep the rubber bumpers clean.

Discontinue the use of the gate if it becomes damaged, broken or disassembled.


Sample tested to meet U.S. Federal ASTM and other safety requirements.